


GBP910D

HYDRAULIC POWERUNIT



DESCRIPTION:

The GBP910D Hydraulic Powerunit is a portable power source designed to operate a wide range of hydraulic installation tools. The unit air powered, air actuated and delivers up to 10,000 psi working pressure. The trigger on the installation tool remotely controls the hydraulic fluid directional flow. The unit consists of a two position air hydraulic pump, four way control valve and relief valve mounted on the reservoir.

The rapid tool piston movement is obtained through a higher (50 cubic inches a minute) output pump. Quick disconnect hydraulic couplings and air control socket are included to attach the equipment hydraulic hoses and air control tube.

GAGE BILT
MADE IN U.S.A.

GAGE BILT Inc.

44766 Centre Court (586) 226-1500
Clinton Twp. MI 48038 (586) 226-1505 Fax
e-mail:solutions@gagebilt.com / www.gagebilt.com



GBP910D POWERUNIT SPECIFICATIONS



NOTE:

An air line filter-lubricator is highly recommended for proper operation and extended life.

NOTE:

Shipped with Pull pressure at 10,000 psi (68,950 kPa) & Return pressure at 6,000 psi (41,370 kPa) for GB7624. When attaching GB585A set Pull pressure to 5,400-5,700 psi (37,350-39,300 kPa) & Return pressure 2,200-2,400 psi (15,200-16,500 kPa).

Width	13.0 inches
Length	20.5 inches
Height.....	14.0 inches
Reservoir Capacity	2 gallons
Power Source - compressed air	90-100 psi
Air Consumption (continuous operation):	62 CFM
Remote Control-Air piloted 4-way valve actuated by a trigger in the tool	
Motor	Air Motor
Pump - Air Hydraulic, Rapid Advance and Swage	50 cu. in./min. @ 5000 psi
Output Pressure:	
Pull	Adjustable to 10,000 psi.

Operating temperature:

Ambient	min. 0° F	-18° C
Hydraulic Fluid...max. 140° F	65° C	

Hydraulic Fluid:

Good Quality Hydraulic Oil.